



400 Series Addressable Weatherproof Manual Call Point

KAL455E

The KAL400 Series consists of a complete range of interfaces developed for input and output control in the KSA700 and FP1500 addressable fire systems from GE Security. The KAL455E is an addressable manual call point for manual fire activation for outdoor use. Up to 125 KAL400 series devices may be installed on every loop. Device addressing is done via easy to use DIP switches.

Specifications

Supply voltage	22-35 VDC
Current consumption	
Quiescent	< 250 microA
Alarm	< 2.5 mA
Environmental	
Operating temperature	-10°C to +70°C
Storage temperature	-20°C to +70°C
Operating humidity (non condensing)	10-95 %
Ingress Protection	IP67
Physical	
Cable specification	0.8 to 2.5 mm ²
Dimensions (L x W x H)	97.5 x 93 x 27.5 mm
Weight	187 g



Ordering Information

KAL455E	400 Series Addressable Weatherproof Manual Call Point
DMN782	Hinged transparent MCP protection cover
DMN798	Breakable Seal for Manual Call Points
DMN800	Resettable Element for Manual Call Point

- Easy numeric addressing
- Loop powered
- Local test facility
- Aesthetically pleasing
- Local status indication
- Part of family of I/O modules consisting of:
 - Conventional Zone Monitors
 - Digital Input Modules
 - Extinguishing Control Modules
 - Isolator Modules
 - Standard Manual Call Points
 - Output Units
 - Fire Door Controllers
 - Supervised Output Units
- Wide range of accessories
- Weatherproof