Fire sounder, multi tone, shallow base



The AS363 is a general purpose electronic sounder for fire alarm applications. Which features a special base containing all wiring connections and allow for easy removal/placement of the sounder.

Specifications

Operation	Continuous
Supply voltage	
EN54-3 / fire applications	17 - 60 VDC
non-fire applications	9 - 60 VDC
Current consumption	
(see tone table in manual)	4 - 41mA @ 24 VDC
Sound output @ 1 metre	
(see tone table in manual)	94 to 106dB(A)
Number of tones	32
Automatic synchronisation	Phased start
Line monitoring input	Polarised input
Housing	High impact polycarbonate
Ingress protection	IP21
Operating temperature	-25°C to +70°C
Dimensions (Ø x D)	
Shallow base	100 x 81 mm
Weight	215g
Color	Red

Ordering Information

AS363 AS363W AS363M AS364 AS364W AS3664M AS366 AS366W AS367 AS367W AS368	Fire sounder, multi tone, shallow base Fire sounder, multi tone, shallow base, white Sounder, multi tone, shallow base, mains powered Fire sounder, multi tone, deep base Fire sounder, multi tone, deep base, white Sounder, multi tone, deep base, white Sounder-beacon, multi tone, shallow base Sounder-beacon, multi tone, shallow base, white Sounder-beacon, multi tone, deep base Sounder-beacon, multi tone, deep base, white Base sounder, multi tone, deep base, white
AS368 AS368W	Base sounder, multi tone, red Base sounder, multi tone, white



- · High sound output
- Low current consumption
- 32 Tones user selectable
- Automatic syncronisation
- Volume control
- Anti-Tamper locking mechanism
- Shallow mouting base
- Wiring directly to base
- Two stage alarm
- VdS Approved